



BARGE: GM 1014

INNAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8
2 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
3 PORT	- 00-1/2	00-1/2	- 01-0/8	01-0/8	- 01-1/2	01-1/2	- 02-0/8	02-0/8	- 02-1/2	02-1/2	- 03-1/8	03-1/8
3 STBD	- 00-1/2	00-1/2	- 01-0/8	01-0/8	- 01-1/2	01-1/2	- 02-0/8	02-0/8	- 02-1/2	02-1/2	- 03-1/8	03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
 AFT DRAFT = 4'-00"
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS 01-0/8"
 FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED INNAGE IS 4'-01'

LENGTH BETWEEN DRAFT MARKS: 262'-00"

May 26, 2016

