



BARGE: GM 1016

INNAGE TRIM TABLE
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
1 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 PORT	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
2 STBD	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-1/8	00-1/8	- 00-1/8	00-1/8
3 PORT	- 00-1/2	00-1/2	- 01-0/8	01-0/8	- 01-5/8	01-5/8	- 02-1/8	02-1/8	- 02-5/8	02-5/8	- 03-1/8	03-1/8
3 STBD	- 00-1/2	00-1/2	- 01-0/8	01-0/8	- 01-5/8	01-5/8	- 02-1/8	02-1/8	- 02-5/8	02-5/8	- 03-1/8	03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"
AFT DRAFT = 4'-00"
DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS 01-0/8"
FOR A MEASURED INNAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED INNAGE IS 4'-01'

LENGTH BETWEEN DRAFT MARKS: 262'-00"

June 24, 2016



BARGE: GM 1016
JEFFBOAT 15-2110

2 PORT
INNAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-01 3/8"

Table with 25 columns (0 to 15 FT.) and 25 rows (0 to 15 FT.). Each cell contains a numerical value representing capacity in barrels. The table is organized into a grid where the first row and first column represent 0 feet, and the last row and last column represent 15 feet. Intermediate rows and columns are labeled with 1/4, 1/2, and 3/4 increments.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 06/08/2016 BY: JM
DATE COMPUTED: 06/23/2016 BY: CL
DATE ISSUED: 06/24/2016

Signature of the responsible party

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 15'-11"

Table with 24 columns (0 to 15 FT) and 24 rows (0 to 15 FT) showing capacity values in barrels of 42 U.S. gallons for various gauge heights.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 06/08/2016 BY: JM
DATE COMPUTED: 06/23/2016 BY: CL
DATE ISSUED: 06/24/2016

