



# BARGE: GM 1016

ULLAGE TRIM TABLE  
"HERMETIC"

	1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.	
	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>	<u>BOW</u>	<u>STERN</u>
1 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
1 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 PORT	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
2 STBD	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-0/8	- 00-0/8	00-1/8	- 00-1/8	00-1/8	- 00-1/8
3 PORT	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-5/8	- 01-5/8	02-1/8	- 02-1/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8
3 STBD	00-1/2	- 00-1/2	01-0/8	- 01-0/8	01-5/8	- 01-5/8	02-1/8	- 02-1/8	02-5/8	- 02-5/8	03-1/8	- 03-1/8

(ALL MEASUREMENTS ABOVE ARE IN INCHES)

EXAMPLE FOR ABOVE TRIM CORRECTIONS:

FWD. DRAFT = 2'-00"  
 AFT DRAFT = 4'-00"  
 DIFF. = 2'-00" (DOWN BY STERN)

THE CORRECTION FOR 2'-00" TRIM DOWN BY STERN FOR 3 PORT IS - 01-0/8"  
 FOR A MEASURED ULLAGE GAUGE OF 4'-00" ON 3 PORT, THE TRIM CORRECTED ULLAGE IS 3'-11"

LENGTH BETWEEN DRAFT MARKS: 262'-00"

June 24, 2016







BARGE: GM 1016
JEFFBOAT 15-2110

2 PORT
ULLAGE TABLE

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-01 3/8"

Table with 25 columns (IN, 1 FT., IN, 2 FT., IN, 3 FT., IN, 4 FT., IN, 5 FT., IN, 6 FT., IN, 7 FT., IN, 8 FT., IN, 9 FT., IN, 10 FT., IN, 11 FT., IN, 12 FT., IN, 13 FT., IN, 14 FT., IN, 15 FT., IN, 16 FT.) and 19 rows of capacity data.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 06/08/2016 BY: JM
DATE COMPUTED: 06/23/2016 BY: CL
DATE ISSUED: 06/24/2016

Signature

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

FOR MANUAL GAUGING AT 2" BALL VALVE LOCATED NEAR GEOMETRIC CENTER OF TANK

REFERENCE GAUGE HEIGHT: 16'-00 3/4"

Table with 24 columns (0 to 16 FT.) and 24 rows (0 to 16 FT.). Each cell contains capacity values for 1/4, 1/2, and 3/4 inch measurements.

THIS CHART IS CERTIFIED FOR THE ABOVE NAMED TANK ONLY. NO CHANGES OF ANY KIND CAN BE MADE WITHOUT THE WRITTEN CONSENT OF OUR COMPANY.

NOTE: GAUGE POINT: TO TOP LIP OF BALL VALVE, ON 18" DECK PIPE.  
NOTE: GAUGE POINT LOCATED NEAR GEOMETRIC CENTER OF TANK  
NOTE: FOR GREATER ACCURACY, BARGE SHOULD BE UPRIGHT AND ON EVEN KEEL  
NOTE: MEASURED AND COMPUTED IN ACCORDANCE WITH API MPMS 2.7

DATE STRAPPED: 06/08/2016 BY: JM  
DATE COMPUTED: 06/23/2016 BY: CL  
DATE ISSUED: 06/24/2016





