



BARGE "GRIFCO 3002"

GRIFCO TRANSPORTATION COMPANY

HULL NO. 2140-2

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.	TANKS NO. 4 PORT OR STAR.
0'-6"	(-) 0'-0 3/4"	(-) 0'-0 5/8"	(-) 0'-0 3/4"	(+) 0'-0 3/4"
1'-0"	(-) 0'-1 1/2"	(-) 0'-1 3/8"	(-) 0'-1 1/2"	(+) 0'-1 1/2"
1'-6"	(-) 0'-2 1/4"	(-) 0'-2"	(-) 0'-2 1/4"	(+) 0'-2 1/4"
2'-0"	(-) 0'-3"	(-) 0'-2 3/4"	(-) 0'-3"	(+) 0'-3"
2'-6"	(-) 0'-3 3/4"	(-) 0'-3 3/8"	(-) 0'-3 3/4"	(+) 0'-3 3/4"
3'-0"	(-) 0'-4 1/2"	(-) 0'-4"	(-) 0'-4 1/2"	(+) 0'-4 1/2"
3'-6"	(-) 0'-5 1/4"	(-) 0'-4 3/4"	(-) 0'-5 1/4"	(+) 0'-5 1/4"
4'-0"	(-) 0'-6"	(-) 0'-5 3/8"	(-) 0'-6"	(+) 0'-6"
4'-6"	(-) 0'-6 3/4"	(-) 0'-6"	(-) 0'-6 3/4"	(+) 0'-6 3/4"
5'-0"	(-) 0'-7 1/2"	(-) 0'-6 3/4"	(-) 0'-7 1/2"	(+) 0'-7 1/2"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 6/9/05

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3002" GRIFCO TRANSPORTATION COMPANY

INNAGE TABLE

TANK NO.

1 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

Table with columns for height (0 FT. to 15 FT.) and corresponding capacity values for various tank sections (0, 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15).

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/9/05

PORT REFERENCE GAUGE HEIGHT : 17'-6 3/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

STAR REFERENCE GAUGE HEIGHT : 17'-7" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3002" GRIFCO TRANSPORTATION COMPANY INNAGE TABLE

TANK NO. 2 PORT OR STAR

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

Table with 21 columns (0 FT. to 15 FT.) and 41 rows of capacity data in barrels.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/9/05

PORT REFERENCE GAUGE HEIGHT : 17-7" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

STAR REFERENCE GAUGE HEIGHT : 17-7 1/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3002"
GRIFCO TRANSPORTATION COMPANY

OUTAGE TABLE

TANK NO.
1 PORT

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

Table with columns for gauge height (1 FT. to 17 FT.) and rows for liquid levels (0, 1/4, 1/2, 3/4) at each height. Each cell contains a numerical value representing the measurement.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/9/05

REFERENCE GAUGE HEIGHT: 17'-6 3/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Signature of Inspector

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3002"
GRIFCO TRANSPORTATION COMPANY
OUTAGE TABLE

TANK NO.
2 STAR

HULL NO. 2140-2

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

Table with columns for 1 FT. to 17 FT. and rows for gauge depths 0, 1/4, 1/2, 3/4. Each cell contains numerical data representing measurements in various units.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

REFERENCE GAUGE HEIGHT: 17'-7 1/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

STRAPPED: 6/9/05

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



BARGE "GRIFCO 3002" GRIFCO TRANSPORTATION COMPANY

TANK NO. 3 PORT

OUTAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

Table with 17 columns representing gauge heights from 1 FT. to 17 FT. and multiple rows for each height, containing numerical data for capacity measurements.

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/9/05

REFERENCE GAUGE HEIGHT : 17'-7 1/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Inspector signature and INSPECTORATE AMERICA CORPORATION text.



**BARGE "GRIFCO 3002"
GRIFCO TRANSPORTATION COMPANY**

**TANK NO.
4 STAR**

OUTAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

N	1 FT.	N	2 FT.	N	3 FT.	N	4 FT.	N	5 FT.	N	6 FT.	N	7 FT.	N	8 FT.	N	9 FT.	N	10 FT.	N	11 FT.	N	12 FT.	N	13 FT.	N	14 FT.	N	15 FT.	N	16 FT.	N	17 FT.
0		0	3,397.75	0	3,339.98	0	3,255.69	0	3,171.40	0	3,057.94	0	2,777.98	0	2,497.52	0	2,217.06	0	1,936.59	0	1,656.13	0	1,375.66	0	1,095.39	0	815.55	0	535.57	0	255.11	0	10.94

CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS

STRAPPED: 6/9/05

REFERENCE GAUGE HEIGHT : 17'-7 1/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.



BARGE "GRIFCO 3002" GRIFCO TRANSPORTATION COMPANY

TANK NO. 4 PORT

OUTAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

Table with 17 columns (1 FT. to 17 FT.) and 17 rows (0 to 17). Each cell contains numerical data representing measurements. Includes a note 'CAPACITIES GIVEN IN BARRELS OF 42 U.S. GALLONS' at the bottom left of the table area.

STRAPPED: 6/9/05

REFERENCE GAUGE HEIGHT: 17'-7 1/2" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

Handwritten signature and 'INSPECTORATE AMERICA CORPORATION' text.



BARGE "GRIFCO 3002"
GRIFCO TRANSPORTATION COMPANY
 INNAGE TABLE

TANK NO.
STAR FUEL DECK TANK

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0	0	1,298	0	3,060	0	4,916	0	6,611	0	0	0	0	0	0
1/4	16	1/4	1,332	1/4	3,098	1/4	4,954	1/4	6,642	1/4	1/4	1/4	1/4	1/4	1/4
1/2	32	1/2	1,366	1/2	3,137	1/2	4,992	1/2	6,673	1/2	1/2	1/2	1/2	1/2	1/2
3/4	48	3/4	1,400	3/4	3,176	3/4	5,030	3/4	6,704	3/4	3/4	3/4	3/4	3/4	3/4
1	64	1	1,434	1	3,214	1	5,067	1	6,734	1	1	1	1	1	1
1/4	84	1/4	1,469	1/4	3,253	1/4	5,105	1/4	6,764	1/4	1/4	1/4	1/4	1/4	1/4
1/2	104	1/2	1,504	1/2	3,292	1/2	5,142	1/2	6,794	1/2	1/2	1/2	1/2	1/2	1/2
3/4	124	3/4	1,539	3/4	3,331	3/4	5,180	3/4	6,824	3/4	3/4	3/4	3/4	3/4	3/4
2	144	2	1,573	2	3,369	2	5,217	2	6,854	2	2	2	2	2	2
1/4	167	1/4	1,609	1/4	3,408	1/4	5,254	1/4	6,883	1/4	1/4	1/4	1/4	1/4	1/4
1/2	189	1/2	1,644	1/2	3,447	1/2	5,292	1/2	6,912	1/2	1/2	1/2	1/2	1/2	1/2
3/4	212	3/4	1,679	3/4	3,486	3/4	5,329	3/4	6,941	3/4	3/4	3/4	3/4	3/4	3/4
3	234	3	1,715	3	3,525	3	5,366	3	6,969	3	3	3	3	3	3
1/4	259	1/4	1,751	1/4	3,564	1/4	5,403	1/4	6,997	1/4	1/4	1/4	1/4	1/4	1/4
1/2	283	1/2	1,786	1/2	3,603	1/2	5,439	1/2	7,025	1/2	1/2	1/2	1/2	1/2	1/2
3/4	308	3/4	1,822	3/4	3,642	3/4	5,476	3/4	7,052	3/4	3/4	3/4	3/4	3/4	3/4
4	332	4	1,858	4	3,680	4	5,513	4	7,080	4	4	4	4	4	4
1/4	359	1/4	1,895	1/4	3,719	1/4	5,549	1/4	7,106	1/4	1/4	1/4	1/4	1/4	1/4
1/2	385	1/2	1,931	1/2	3,758	1/2	5,586	1/2	7,132	1/2	1/2	1/2	1/2	1/2	1/2
3/4	411	3/4	1,967	3/4	3,797	3/4	5,622	3/4	7,158	3/4	3/4	3/4	3/4	3/4	3/4
5	437	5	2,004	5	3,836	5	5,658	5	7,184	5	5	5	5	5	5
1/4	464	1/4	2,040	1/4	3,875	1/4	5,694	1/4	7,209	1/4	1/4	1/4	1/4	1/4	1/4
1/2	492	1/2	2,077	1/2	3,914	1/2	5,730	1/2	7,233	1/2	1/2	1/2	1/2	1/2	1/2
3/4	520	3/4	2,114	3/4	3,953	3/4	5,766	3/4	7,258	3/4	3/4	3/4	3/4	3/4	3/4
6	547	6	2,151	6	3,992	6	5,802	6	7,282	6	6	6	6	6	6
1/4	576	1/4	2,188	1/4	4,031	1/4	5,837	1/4	7,305	1/4	1/4	1/4	1/4	1/4	1/4
1/2	605	1/2	2,225	1/2	4,069	1/2	5,872	1/2	7,327	1/2	1/2	1/2	1/2	1/2	1/2
3/4	634	3/4	2,262	3/4	4,108	3/4	5,908	3/4	7,350	3/4	3/4	3/4	3/4	3/4	3/4
7	662	7	2,299	7	4,147	7	5,943	7	7,372	7	7	7	7	7	7
1/4	692	1/4	2,337	1/4	4,186	1/4	5,978	1/4	7,392	1/4	1/4	1/4	1/4	1/4	1/4
1/2	722	1/2	2,374	1/2	4,225	1/2	6,013	1/2	7,412	1/2	1/2	1/2	1/2	1/2	1/2
3/4	752	3/4	2,412	3/4	4,263	3/4	6,047	3/4	7,432	3/4	3/4	3/4	3/4	3/4	3/4
8	782	8	2,449	8	4,302	8	6,082	8	7,452	8	8	8	8	8	8
1/4	813	1/4	2,487	1/4	4,341	1/4	6,116	1/4	7,468	1/4	1/4	1/4	1/4	1/4	1/4
1/2	844	1/2	2,525	1/2	4,379	1/2	6,150	1/2	7,484	1/2	1/2	1/2	1/2	1/2	1/2
3/4	875	3/4	2,563	3/4	4,418	3/4	6,185	3/4	7,501	3/4	3/4	3/4	3/4	3/4	3/4
9	906	9	2,600	9	4,457	9	6,219	9	7,517	9	9	9	9	9	9
1/4	938	1/4	2,639	1/4	4,495	1/4	6,252	1/4	7,531	1/4	1/4	1/4	1/4	1/4	1/4
1/2	970	1/2	2,677	1/2	4,534	1/2	6,286	1/2	7,544	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,001	3/4	2,715	3/4	4,572	3/4	6,319	3/4	7,557	3/4	3/4	3/4	3/4	3/4	3/4
10	1,033	10	2,753	10	4,611	10	6,353	10	7,570	10	10	10	10	10	10
1/4	1,066	1/4	2,791	1/4	4,649	1/4	6,385	1/4	7,582	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1,099	1/2	2,829	1/2	4,687	1/2	6,418	1/2	7,593	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,131	3/4	2,868	3/4	4,726	3/4	6,451	3/4	7,604	3/4	3/4	3/4	3/4	3/4	3/4
11	1,164	11	2,906	11	4,764	11	6,483	11	7,615	11	11	11	11	11	11
1/4	1,197	1/4	2,944	1/4	4,802	1/4	6,515	1/4	7,625	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1,231	1/2	2,983	1/2	4,840	1/2	6,547	1/2	7,635	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,264	3/4	3,021	3/4	4,878	3/4	6,579	3/4	7,645	3/4	3/4	3/4	3/4	3/4	3/4

CAPACITIES GIVEN IN U.S. GALLONS

STRAPPED:6/9/05

REFERENCE GAUGE HEIGHT : 5'-7" (TO RIM OF 10" DIAMETER HATCH
 OPPOSITE HINGE LOCATED NEAR AFT END OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
 IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
 ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3002"
GRIFCO TRANSPORTATION COMPANY
 INNAGE TABLE

TANK NO.
PORT FUEL DECK TANK

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2140-2

	0 FT.	1 FT.	2 FT.	3 FT.	4 FT.	5 FT.	6 FT.	7 FT.	8 FT.	9 FT.	10 FT.	11 FT.	12 FT.	13 FT.	14 FT.
0	0	0	1,298	0	3,060	0	4,916	0	6,611	0	0	0	0	0	0
1/4	16	1/4	1,332	1/4	3,098	1/4	4,954	1/4	6,642	1/4	1/4	1/4	1/4	1/4	1/4
1/2	32	1/2	1,366	1/2	3,137	1/2	4,992	1/2	6,673	1/2	1/2	1/2	1/2	1/2	1/2
3/4	48	3/4	1,400	3/4	3,176	3/4	5,030	3/4	6,704	3/4	3/4	3/4	3/4	3/4	3/4
1	64	1	1,434	1	3,214	1	5,067	1	6,734	1	1	1	1	1	1
1/4	84	1/4	1,469	1/4	3,253	1/4	5,105	1/4	6,764	1/4	1/4	1/4	1/4	1/4	1/4
1/2	104	1/2	1,504	1/2	3,292	1/2	5,142	1/2	6,794	1/2	1/2	1/2	1/2	1/2	1/2
3/4	124	3/4	1,539	3/4	3,331	3/4	5,180	3/4	6,824	3/4	3/4	3/4	3/4	3/4	3/4
2	144	2	1,573	2	3,369	2	5,217	2	6,854	2	2	2	2	2	2
1/4	167	1/4	1,609	1/4	3,408	1/4	5,254	1/4	6,883	1/4	1/4	1/4	1/4	1/4	1/4
1/2	189	1/2	1,644	1/2	3,447	1/2	5,292	1/2	6,912	1/2	1/2	1/2	1/2	1/2	1/2
3/4	212	3/4	1,679	3/4	3,486	3/4	5,329	3/4	6,941	3/4	3/4	3/4	3/4	3/4	3/4
3	234	3	1,715	3	3,525	3	5,366	3	6,969	3	3	3	3	3	3
1/4	259	1/4	1,751	1/4	3,564	1/4	5,403	1/4	6,997	1/4	1/4	1/4	1/4	1/4	1/4
1/2	283	1/2	1,786	1/2	3,603	1/2	5,439	1/2	7,025	1/2	1/2	1/2	1/2	1/2	1/2
3/4	308	3/4	1,822	3/4	3,642	3/4	5,476	3/4	7,052	3/4	3/4	3/4	3/4	3/4	3/4
4	332	4	1,858	4	3,680	4	5,513	4	7,080	4	4	4	4	4	4
1/4	359	1/4	1,895	1/4	3,719	1/4	5,549	1/4	7,106	1/4	1/4	1/4	1/4	1/4	1/4
1/2	385	1/2	1,931	1/2	3,758	1/2	5,586	1/2	7,132	1/2	1/2	1/2	1/2	1/2	1/2
3/4	411	3/4	1,967	3/4	3,797	3/4	5,622	3/4	7,158	3/4	3/4	3/4	3/4	3/4	3/4
5	437	5	2,004	5	3,836	5	5,658	5	7,184	5	5	5	5	5	5
1/4	464	1/4	2,040	1/4	3,875	1/4	5,694	1/4	7,209	1/4	1/4	1/4	1/4	1/4	1/4
1/2	492	1/2	2,077	1/2	3,914	1/2	5,730	1/2	7,233	1/2	1/2	1/2	1/2	1/2	1/2
3/4	520	3/4	2,114	3/4	3,953	3/4	5,766	3/4	7,258	3/4	3/4	3/4	3/4	3/4	3/4
6	547	6	2,151	6	3,992	6	5,802	6	7,282	6	6	6	6	6	6
1/4	576	1/4	2,188	1/4	4,031	1/4	5,837	1/4	7,305	1/4	1/4	1/4	1/4	1/4	1/4
1/2	605	1/2	2,225	1/2	4,069	1/2	5,872	1/2	7,327	1/2	1/2	1/2	1/2	1/2	1/2
3/4	634	3/4	2,262	3/4	4,108	3/4	5,908	3/4	7,350	3/4	3/4	3/4	3/4	3/4	3/4
7	662	7	2,299	7	4,147	7	5,943	7	7,372	7	7	7	7	7	7
1/4	692	1/4	2,337	1/4	4,186	1/4	5,978	1/4	7,392	1/4	1/4	1/4	1/4	1/4	1/4
1/2	722	1/2	2,374	1/2	4,225	1/2	6,013	1/2	7,412	1/2	1/2	1/2	1/2	1/2	1/2
3/4	752	3/4	2,412	3/4	4,263	3/4	6,047	3/4	7,432	3/4	3/4	3/4	3/4	3/4	3/4
8	782	8	2,449	8	4,302	8	6,082	8	7,452	8	8	8	8	8	8
1/4	813	1/4	2,487	1/4	4,341	1/4	6,116	1/4	7,468	1/4	1/4	1/4	1/4	1/4	1/4
1/2	844	1/2	2,525	1/2	4,379	1/2	6,150	1/2	7,484	1/2	1/2	1/2	1/2	1/2	1/2
3/4	875	3/4	2,563	3/4	4,418	3/4	6,185	3/4	7,501	3/4	3/4	3/4	3/4	3/4	3/4
9	906	9	2,600	9	4,457	9	6,219	9	7,517	9	9	9	9	9	9
1/4	938	1/4	2,639	1/4	4,495	1/4	6,252	1/4	7,532	1/4	1/4	1/4	1/4	1/4	1/4
1/2	970	1/2	2,677	1/2	4,534	1/2	6,286	1/2	7,546	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,001	3/4	2,715	3/4	4,572	3/4	6,319	3/4	7,560	3/4	3/4	3/4	3/4	3/4	3/4
10	1,033	10	2,753	10	4,611	10	6,353	10	7,574	10	10	10	10	10	10
1/4	1,066	1/4	2,791	1/4	4,649	1/4	6,385	1/4	7,588	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1,099	1/2	2,829	1/2	4,687	1/2	6,418	1/2	7,602	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,131	3/4	2,868	3/4	4,726	3/4	6,451	3/4	7,616	3/4	3/4	3/4	3/4	3/4	3/4
11	1,164	11	2,906	11	4,764	11	6,483	11	7,630	11	11	11	11	11	11
1/4	1,197	1/4	2,944	1/4	4,802	1/4	6,515	1/4	7,644	1/4	1/4	1/4	1/4	1/4	1/4
1/2	1,231	1/2	2,983	1/2	4,840	1/2	6,547	1/2	7,658	1/2	1/2	1/2	1/2	1/2	1/2
3/4	1,264	3/4	3,021	3/4	4,878	3/4	6,579	3/4	7,672	3/4	3/4	3/4	3/4	3/4	3/4

CAPACITIES GIVEN IN U.S. GALLONS

STRAPPED:6/9/05

REFERENCE GAUGE HEIGHT : 5'-7" (TO RIM OF 10" DIAMETER HATCH
 OPPOSITE HINGE LOCATED NEAR AFT END OF TANK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE
 IN ACCORDANCE WITH APPLICABLE API STANDARDS AND
 ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION