



BARGE "GRIFCO 3005"

GRIFCO TRANSPORTATION COMPANY

HULL NO. 2141-2

CORRECTION TABLE FOR TRIM AFT.

FOR INNAGE GAUGES ONLY

TRIM	TANKS NO. 1 PORT OR STAR.	TANKS NO. 2 PORT OR STAR.	TANKS NO. 3 PORT OR STAR.	TANKS NO. 4 PORT OR STAR.
0'-6"	(-) 0'-0 5/8"	(-) 0'-0 5/8"	(-) 0'-0 5/8"	(+) 0'-0 3/4"
1'-0"	(-) 0'-1 1/4"	(-) 0'-1 3/8"	(-) 0'-1 3/8"	(+) 0'-1 1/2"
1'-6"	(-) 0'-1 7/8"	(-) 0'-2"	(-) 0'-2"	(+) 0'-2 1/4"
2'-0"	(-) 0'-2 1/2"	(-) 0'-2 3/4"	(-) 0'-2 3/4"	(+) 0'-3"
2'-6"	(-) 0'-3 1/8"	(-) 0'-3 3/8"	(-) 0'-3 3/8"	(+) 0'-3 3/4"
3'-0"	(-) 0'-3 3/4"	(-) 0'-4"	(-) 0'-4"	(+) 0'-4 1/2"
3'-6"	(-) 0'-4 1/2"	(-) 0'-4 3/4"	(-) 0'-4 3/4"	(+) 0'-5 1/4"
4'-0"	(-) 0'-5 1/8"	(-) 0'-5 3/8"	(-) 0'-5 3/8"	(+) 0'-6"
4'-6"	(-) 0'-5 3/4"	(-) 0'-6"	(-) 0'-6"	(+) 0'-6 5/8"
5'-0"	(-) 0'-6 3/8"	(-) 0'-6 3/4"	(-) 0'-6 3/4"	(+) 0'-7 3/8"

NOTE: FOR TRIM FWD., REVERSE SIGNS.

NOTE: IF LIQUID SURFACE TOUCHES TANK BOTTOM OR DECK WHEN GAUGED,
TRIM CORRECTIONS ARE NOT ACCURATE.

NOTE: FOR "OUTAGE" GAUGES, REVERSE SIGNS.

DATE: 7/26/05

BY:

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3005"

GRIFCO TRANSPORTATION COMPANY

INMAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2141-2

Table with columns for draft (0 FT to 15 FT), tank number (1 to 14), and capacity in barrels and gallons. Includes a signature and company name at the top.

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

INSPECTORATE AMERICA CORPORATION



BARGE "GRIFCO 3005" GRIFCO TRANSPORTATION COMPANY

TANK NO. 3 PORT OR STAR

INNAGE TABLE

BARGE SHOULD BE ON EVEN-LEVEL KEEL WHEN GAUGES ARE TAKEN

HULL NO. 2141-2

0 FT.		1 FT.		2 FT.		3 FT.		4 FT.		5 FT.		6 FT.		7 FT.		8 FT.		9 FT.		10 FT.		11 FT.		12 FT.		13 FT.		14 FT.		15 FT.	
0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	
1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	
2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	
3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	3	
4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	
5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	
6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	6	
7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	7	
8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	8	
9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	9	
10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	
11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	
12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	
13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	13	
14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	14	
15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	15	

CAPACITIES GIVEN IN BARRELS OR 42 U.S. GALLONS

PORT REFERENCE GAUGE HEIGHT : 17'-7" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

WE CERTIFY ALL MEASUREMENTS AND COMPUTATIONS ARE IN ACCORDANCE WITH APPLICABLE API STANDARDS AND ARE TRUE AND CORRECT TO THE BEST OF OUR KNOWLEDGE.

STAR REFERENCE GAUGE HEIGHT : 17'-7 1/4" (TO 10" DIAMETER HATCH LOCATED NEAR EXPANSION TRUNK)

INSPECTORATE AMERICA CORPORATION

